

**NAME**

ptftopl, uptftopl – Convert Japanese pTeX font metric (JFM) files to property list

**SYNOPSIS**

**ptftopl** [*OPTIONS*] *tfm\_name*[.tfm] [*pl\_name*[.pl]]

**DESCRIPTION**

The **ptftopl** program translates a Japanese pTeX font metric (JFM) file to a Japanese property list (JPL) file. It also serves as a TFM/JFM-file validating program.

The **uptftopl** program is a Unicode-enabled version of ptftopl.

In the following sections, we refer to these programs as **(u)ptftopl**.

**(u)ptftopl** is upper compatible with **tftopl**; if the input TFM file is for roman fonts, it is translated into an ordinary property list file. The difference between **ptftopl** and **uptftopl** lies in the internal encoding: when the input is a JFM file, **ptftopl** always treats it as a JIS-encoded JFM; on the other hand, **uptftopl** treats it as a Unicode-encoded JFM by default.

**OPTIONS**

Compared to tftopl, the following option is added to **(u)ptftopl**.

**-kanji** *string*

Sets the output Japanese *Kanji* code. The *string* can be one of the followings:  
*euc* (EUC-JP), *jis* (ISO-2022-JP), *sjis* (Shift\_JIS), *utf8* (UTF-8), *uptex* (UTF-8;  
**uptftopl** only).

When one of *euc*, *jis*, *sjis* or *utf8* is specified, both **ptftopl** and **uptftopl** treats the input JFM as JIS-encoded. When *uptex* is specified with **uptftopl**, it treats the input JFM as Unicode-encoded.

**SEE ALSO**

**ptex**(1).

**AUTHORS**

**(u)ptftopl** is maintained by Japanese T<sub>E</sub>X Development Community <<https://texjp.org>>. For bug reports, open an issue at GitHub repository <<https://github.com/texjporg/tex-jp-build>>, or send an e-mail to <[issue@texjp.org](mailto:issue@texjp.org)>.

This manual page was written by Hironobu Yamashita.